



SOIL SAMPLING CONFIRMS POTENTIAL FOR LARGER MINERALISED SYSTEM AT BRIGGS PORPHYRY COPPER DEPOSIT, QLD

Highlights

- Copper and molybdenum anomalism detected in detailed soil sampling confirms significant upside potential at Briggs, Central Queensland (Inferred Mineral Resource 143Mt @ 0.29% Cu).
- Assays from 100m x 50m spaced soil sampling define a surface geochemical anomaly which is >2,200m long and >950m wide, at >500ppm Cu, and which extends up to 1,200m outside the currently defined mineral resource envelope (Figure 1).



Figure 1 Gridded copper anomalism in new soil sampling showing anomalism extending considerable distances from the Mineral Resource Estimate outline at Briggs. All holes drilled to date shown on this plan.

- The copper geochemistry indicates very significant targets for additional tonnage immediately surrounding the Briggs Central Mineral Resource Estimate.
- The soil sampling also shows that the drilling to date at the Northern and Southern Porphyry targets has not adequately tested these targets.
- A significant molybdenum anomaly has also been defined and will be tested by future drilling.
- Alma has an exclusive option to enter into an Earn-in JV Agreement over the project and is planning a major drilling campaign expected to commence in late-Q2, 2022.



Introduction and Summary

Alma Metals Limited (ASX:ALM, "the Company" or "Alma") is pleased to announce assays from detailed 100m x 50m spaced soil sampling at the Briggs, Mannersley and Fig Tree Hill copper project in Queensland ("Project") (see Figure 2 for location).

This is the first modern program to collect high resolution, low detection level gold and multielement geochemistry across the entire Briggs porphyry system and represents a significant advance on patchy historical soil sampling undertaken by multiple parties in previous decades.

The new assays define extensive copper and molybdenum anomalism surrounding the known Briggs Central Mineral Resource (currently 143Mt @ 0.29% Cu in Inferred Resources at a 0.2% Cu cut-off grade) and the Northern and Southern porphyry targets that outcrop along strike. The soil sampling results highlight several targets for drilling to expand the mineral resource estimate.

This soil sampling program forms a significant component of the exploration commitment made by Alma under an Option and Earn-In Joint Venture Agreement signed with Canterbury Resources Limited ("Canterbury") in August 2021 (refer ASX release dated 18 August 2021), through which Alma can ultimately reach 70% ownership of the project.



Figure 2 Location map showing proximity of the Briggs, Mannersley and Fig Tree Hill copper project to major infrastructure including ports, rail and power.

Soil Sampling Results

A total of 643 soil samples on a nominal 100m x 50m grid have been collected over the Briggs porphyry copper system in Queensland. This represents approximately 70% of the planned survey and covers the majority of the known mineralisation.



Assay results from the soil sampling have confirmed extensive copper and molybdenum anomalism which extends for up to 750m along strike from the Briggs Mineral Resource Estimate.

Key observations from the assay data are as follows:

- Copper anomalism peaks at 4,710ppm Cu (0.47% Cu) and defines a large anomaly measuring more than 2200m along strike and over 950m across strike at >500ppm Cu.
- Within the >500ppm Cu anomaly there are several clusters of >1,000ppm Cu which reflect the known mineralised centres at Briggs Central and the Northern and Southern Porphyry Targets (Figure 3).
- There is a very strong correlation between surface soil sampling geochemistry and the underlying geology as evident from outcrop.
- The copper geochemistry indicates very significant targets for additional tonnage immediately surrounding the Briggs Central Mineral Resource Estimate.
- The soil sampling also shows that the drilling to date at the Northern and Southern Porphyry targets has not adequately tested these targets.



Figure 3 Geochemical soil sampling showing copper assays for each sample point overlaid on gridded copper in soils.

- A large molybdenum anomaly (>20ppm Mo) with a peak value of 84ppm partially surrounds the copper anomaly at Briggs Central, indicating a zoned system consistent with multiple mineralised events as previously documented from drill core (Figure 4).
- The soil sampling results are currently being integrated with geological mapping, spectral analysis and previously captured geophysical survey data to prioritise drill targets.





Figure 4 Geochemical soil sampling showing molybdenum assays at each sample point overlaid on gridded molybdenum in soils.

Next Steps

- Based on these results, Alma expects to execute the option to enter the Earn-in Phase of the Briggs, Mannersley and Fig Tree Hill joint venture in the coming weeks.
- Follow-up drilling to expand the Inferred Mineral Resource at Briggs is currently being planned for commencement after the wet season, likely to commence later this quarter.
- A total of 20 core holes for approximately 5,000m will be drilled to include testing the immediate upside around the published resource, the newly defined molybdenum anomaly and both the Northern and Southern Porphyry Targets (Figure 5).

This announcement is authorised for release by Executive Director, Frazer Tabeart.

For further information, please contact the Company directly:

+61 8 6465 5500

investors@almametals.com.au





Figure 5 Planned core drilling locations overlain on gridded and contoured copper in soils geochemistry and showing (in black) the current mineral resource estimate outline at Briggs Central. Note the absence of drilling in much of the copper anomaly.

COMPETENT PERSONS STATEMENT

The Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (the 'JORC Code') sets out minimum standards, recommendations and guidelines for Public Reporting in Australasia of Exploration Results, Mineral Resources and Ore Reserves. The information contained in this announcement has been presented in accordance with the JORC Code (2012 edition) and references to "Measured, Indicated and Inferred Resources" are to those terms as defined in the JORC Code (2012 edition).

The information in this report relating to exploration activities and results is based on information reviewed by Dr Frazer Tabeart (Executive Director of Alma Metals Limited). Dr Tabeart is a member of the Australian Institute of Geoscientists. Dr Tabeart is a qualified geologist and has sufficient experience which is relevant to the style of mineralisation and type of deposits under consideration and to the activity which he is undertaking, to qualify as Competent Persons as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Dr Tabeart consents to the inclusion in the ASX release of the matters based on their information in the form and context in which it appears.

FORWARD LOOKING STATEMENTS:

Any forward-looking information contained in this news release is made as of the date of this news release. Except as required under applicable securities legislation, Alma Metals does not intend, and does not assume any obligation, to update this forward-looking information. Any forward-looking information contained in this news release is based on numerous assumptions and is subject to all of the risks and uncertainties inherent in the Company's business, including risks inherent in resource exploration and development. As a result, actual results may vary materially from those described in the forward-looking information. Readers are cautioned not to place undue reliance on forward-looking information due to the inherent uncertainty thereof.

ALMA[‡]METALS

APPENDIX 1 - JORC TABLES

JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 Soil samples were collected on a nominal 100m x 50m grid. Samples were collected from approximately 15-20cm below the surface and were sieved in the field to -2mm to collect ~500g of sieved sample. Samples were dried and sieved in the lab to -180 um and split to produce a 25g charge for analysis by ICP-MS.
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc). 	• N/A as no drilling undertaken.
Sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 Sample were collected from the same soil horizon at each location and the entire sample submitted to the laboratory.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	 Geology and alteration was logged at each sample site. Data was entered into Canterbury's and Alma Metal's geochemical database (Access).



Criteria	JORC Code explanation	Commentary
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 Samples for assay were delivered by Canterbury employees directly to ALS's sample preparation facility at Zillmere (Brisbane). Samples were dried and sieve to -180um (Code PREP41). A 25g charge for assay was taken.
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 Samples were dissolved in aqua regia (partial digest technique suitable for soil sampling) and assayed by ICP mass spectrometer for gold and multiple trace elements (assay technique AuME-ST43) Commercially available Standards (CRM) were inserted at a rate of approximately 5-6 per 100 samples. Blank samples were inserted at a rate of approximately 5-6 per 100 samples. Field duplicates were collected at a rate of approximately 5-6 per 100 samples. Overall, the results of the assaying of the Standards, Blanks and Duplicates did not indicate any material issue with the sample collection, laboratory techniques or assay results. No laboratory duplicates have yet been sent to an alternate laboratory.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data 	N/A for soil sampling.
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 Coordinates of each sample site were recorded in GDA94 MGA Zone 56 using hand-held GPS. This is considered adequate for this stage of exploration. Topographic surface was LIDAR. A 2km by 2km area over the Briggs prospect was Lidar surveyed in 2018 by Helimetrex Pty Ltd completed with ground stations picked up by DGPS.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Samples were collected on a nominal 100m x 50m grid. This is considered appropriate for a detailed soil survey over this type of mineralisation.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 Soil samples were collected on east-west lines on a regular grid designed to test across the regional northwest – southeast structural trend of the Briggs porphyry system. No material sampling bias is believed to have been introduced due to the scale of the mineralised system and the detailed nature of the sampling.



Criteria	JC	DRC Code explanation	C	ommentary
Sample security	•	The measures taken to ensure sample security.	•	The Briggs soil sampling program was under the continuous supervision of the Canterbury site geologist. Samples collected at in the field were sealed in polyweave bags and delivered to ALS's sample prep facility at Zillmere by company employees.
Audits or reviews	•	The results of any audits or reviews of sampling techniques and data.	•	No audits or reviews have been undertaken of sampling techniques or data.

ALMA[‡]METALS

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 EPM19198 (Briggs) and EPM 27317 (Fig Tree) are located 50km west southwest of Gladstone in central Queensland. EPM19198 is 100% owned by Canterbury Resources (CBY). RTX holds a 1.5% NSR interest. EPM27317 is 100% owned by Canterbury Resources (CBY). In August 2021, Canterbury signed an Option and Earn-In Agreement with Alma Metals in relation to its 100% owned Briggs Copper Project which covers the Briggs, Mannersley and Fig Tree Hill tenements (refer to ASX announcement 18th August 2021). During the Option Period, Alma Metals must spend \$750,000 on exploration and assessment activity to gain the right to enter an Earn-In and Joint Venture Agreement for the Project. This soil sampling program at the Briggs copper prospect is expected to fulfill the Option criteria.
Exploration done by other parties	 Acknowledgment and appraisal of exploration by other parties. 	Refer to ALM ASX release 18 August 2021.
Geology	 Deposit type, geological setting and style of mineralisation. 	 Refer to ALM ASX release 18 August 2021. The Briggs porphyry system in a Permo-Triassic porphyry copper-molybdenum system within the northern New England Fold Belt. Mineralisation occurs in stockwork quartz veins and disseminations hosted in felsic intrusions and the enclosing volcanic sediments. Skarn mineralisation in the volcanic sediments has been observed in some percussion drill cuttings.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	Sample location points and assay results for all samples are depicted on the figures in this report.
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values 	• N/A for soil sampling.



	Criteria	JORC Code explanation	Commentary
)		should be clearly stated.	
	Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	• N/A as no drilling reported in this press release.
	Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 Map showing all soil sampling locations and results are included in this report.
	Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	 Plans showing all sample locations and all assays results for copper and molybdenum are included in this press release
	Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	 Previous Exploration Refer to ALM ASX release on 18 August 2021. Metallurgy Preliminary metallurgical test work completed on core from CBY's 2019 Briggs' diamond drilling program indicates high copper recoveries are achievable across all rock types via conventional processing (crush-grind-flotation) – refer ALM ASX release dated 11 April 2022.
	Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 The next phase of drilling is scheduled to commence in the June quarter 2022 and will include infill and strike extension components. The drilling will be a key input for a proposed Scoping Study evaluation of development of large-scale copper mine at Briggs. Design of the drilling program is underway.